

Commercial Refrigeration Equipment General Specification

DD 23" BASE SERIES—DIRECT DRAW DISPENSERS

http://www.Beverage-Air.com

Shallow depth, direct draw dispensers come in two widths of 48" and 72." Depth is 23" from face of door to back of cabinet. Handle projects 1/2."

CABINET CONSTRUCTION

Standard, cabinet exterior construction includes attractive, wear resistant vinyl on steel in black exterior finish. Top is made from heavy-duty stainless steel including drip tray(s) for easy cleaning.

Doors are self-closing and include key locks. Magnetic gaskets provide positive door sealing.

Standard interior construction utilizes galvanized steel walls and ceiling. Reinforced floor and door sills are made from heavyduty stainless steel to provide long lasting service.

Foamed-in-place CFC and HCFC-free polyurethane insulation enhances the structural strength of the cabinet and helps increase energy efficiency.

Three-inch (3") insulated towers are provided. Towers are adapted to have a continuous source of cold air channeled into it to keep beer at its coldest, best quality the moment it is dispensed.

REFRIGERATION

Models feature forced air refrigeration to keep beer in kegs ice cold for dispensing. Refrigeration system uses R134a refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.

ELECTRICAL

Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet. 8' long cord and plug set included.

SPECIAL FEATURES

- Key locks
- Stainless options available



DRAFT BEER EQUIPMENT **DIRECT DRAW DISPENSERS 23" BASE DD SERIES**

MODELS: **DD48/DD48Y** DD72/DD72Y











*Note: Not all markings may apply to all model variations.

Available From:

| Model Specified | Store# |
|-----------------|----------|
| Location | Quantity |



Direct Draw Dispensers, 23" Base Models: DD48, DD48Y, DD72, DD72Y

| MODEL | DD48 | DD48Y | DD72 | DD72Y |
|--|--------------------|--------------------|--------------------|--------------------|
| EXTERNAL DIMENSIONAL DATA | | | | |
| Length Overall (inches) Length Overall (mm) | 48" 1219 | 48" 1219 | 72" 1829 | 72" 1829 |
| Depth Overall (inches) Depth Overall (mm) | 23 1/2" 597 | 23 1/2" 597 | 23 1/2" 597 | 23 1/2" 597 |
| Height Overall— (inches) Height Overall—(mm) | 36" 914 | 36" 914 | 36" 914 | 36" 914 |
| Clear Door Width (inches) | 16 7/16" x 29 1/4" |
| Depth With Door Open 90° | 42 3/4" | 42 3/4" | 42 3/4" | 42 3/4" |
| Number of doors | 2 | 2 | 3 | 3 |
| INTERNAL DIMENSIONAL DATA | | | | |
| NET Capacity (cubic ft.) NET Capacity (Liters) | 12.1 343 | 12.1 343 | 20.5 581 | 20.5 581 |
| Internal Length Overall (inches) Internal Length Overall (mm) | 36" 914 | 36" 914 | 60" 1524 | 60" 1524 |
| Internal Depth Overall (inches) Internal Depth Overall (mm) | 18 1/2" 470 | 18 1/2" 470 | 18 1/2" 470 | 18 1/2" 470 |
| Internal Height Overall (inches) Internal Height Overall (mm) | 29 1/2" 749 | 29 1/2" 749 | 29 1/2" 749 | 29 1/2" 749 |
| Number of Kegs (straight wall) | 2 | 2 | 3 | 3 |
| ELECTRICAL DATA | | | | |
| Full Load Amperes 115/60/1 | 6 | 5 | 6 | 5 |
| ENERGY CONSUMPTION (KWH) | 4.06 | 3.19 | 4.36 | 3.67 |
| REFRIGERATION DATA | | | | |
| Horsepower | 1/4 | 1/4 | 1/4 | 1/4 |
| WEIGHT DATA | | | | |
| Gross Weight (Crated lbs) | 245 | 245 | 326 | 326 |
| Gross Weight (Crated kg) | 111 | 111 | 148 | 148 |

FRONT DD48 FRONT DD72

_ 23 1/2"

29 1/2"

INSIDE

HT

-21 1/2"

END

36"

PLAN VIEWS

48"











*Note: Not all markings may apply to all model variations.

ELECTRICAL CONNECTION

Units pre-wired at factory and include 8' long cord and plug set.



COMMON END VIEW

BEVERAGE-AIR® CORPORATION